## Residential Water Filters You Have Water Problems?

**BWS Has Solutions:** 

## LANTIS der Dome

## FEATURES:

ELIMINATES IRON STAINING REMOVES SULFUR SMELL. BATTERY BACKUP HOLDS T.O.D./SETTINGS LANTIS VALVE TECHNOLOGY INTEGRAL CHECK VALVE INSTALLED AIR INLET CHECK VALVE INSTALLED DEALER NAME/SERVICE CALL SCROLL SCREEN BACK LIT MICROPROCESSOR CONTROL VALVE WEATHERPROOF NEMA 3R CONTROLLER LINEARY RECIPROCATING PISTON OPERATION NSF CERTIFIED COMPONENTS





MODEL NUMBER SERIES	BTF9	BTF10	<b>BTF12</b>	BTF13	BTF14	BTF16
FILTER MEDIA CAPACITY CF	1	1.5	2	2.5	3	4
APPROX. FREEBOARD	18"	18"	16"	16"	26"	27"
"D" GRAVEL REQUIRED (LBS)	10	10	20	30	40	50
MINERAL TANK (POLYGLASS)	9X48	10X54	12X52	13X54	14X65	16X65
SERVICE FLOW RATE - CONTINUOUS	2.2	2.8	4	5	6	7
SERVICE FLOW RATE - INTERMITTENT	4	5	6	7	8	10
BACKWASH FLOW RATE (GPM)	4.2	5.3	7.5	9	10	15
APPROX. FOOTPRINT	9X11X55	10X12X61	12X13X59	13X13X61	14X14X73	16X16X73
APPROX. SHIPPING WEIGHT (LBS)	30	34	38	42	55	78

THE LANTIS (Lep) 0) the filter offers a creative and dynamic solution to REDUCE IRON AND SULFUR FROM YOUR DRINKING WATER. DURING THE REGENERATION CYCLE, AIR IS DRAWN-IN CREATING AN AIR POCKET ASSISTING IN OXIDATION AND REDUCTION OF FERROUS AND FERRIC IRON, MANGANESE, AND SULFUR ODORS. NO CHEMICAL ADDITIVES OR AIR COMPRESSORS ARE REQUIRED FOR OPERATION OR REGENERATION DUE TO THE SYSTEMS ADVANCED DESIGN AND MICROPROCESSOR CONTROL VALVES.

DURING SERVICE, UNTREATED WATER PASSES THROUGH THE AIR POCKET. THE THE OXIDIZED MINERALS ARE THEN FILTERED WITHIN THE SELECTED MEDIA. THE REGENERATION CYCLE BACKWASHES THE BED AND REPLACES THE AIR POCKET, ALLOWING THE PROCESS TO BEGIN AGAIN.

