

## SCREEN GRADE CALCIUM CARBONATE

# XO WHITE™



XO WHITE™ is a dry ground marble with a coarse particle size that is controlled between 16 and 40 mesh screens. In addition to textured coatings and acid neutralization, XO WHITE is NSF registered for use in water filtration systems.

DAT001CK  
August 2004  
©IMERYS 2000  
Second Edition

All product names are trademarks of IMERYS.

### TYPICAL VALUES

Source:	(M) Marble Hill, GA
% CaCO <sub>3</sub>	95
% Acid Insolubles	2
% SiO <sub>2</sub>	0.3
% Moisture	0.15
% Plus 16 mesh	1
% Minus 40 mesh	10
Hardness (Mohs)	3
Index of refraction	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density (lb/ft <sup>3</sup> )	
Loose	90
Packed	105

**IMERYS**  
100 Mansell Court East  
Suite 300  
Roswell, GA 30076

General:  
Tel: (770) 594.0660  
Fax: (770) 645.3384

Customer Service:  
Tel: (888) 277.9636  
Fax: (770) 645.3631

IMERYS is a business name of IMERYS Pigments, Inc., IMERYS Kaolin, Inc. and IMERYS Marble, Inc. Registered in the USA.

### APPLICATIONS

XO WHITE is suited for use in the following applications:

- Textured Coatings & Stuccos for Interior & Exterior Use
- Water Filtration System (NSF listed)
- Acid Neutralization

This information is believed to be correct. However, this information does not constitute any representation, condition or warranty, nor do we guarantee results to be obtained. All recommendations and sales are made on the condition that we will not be held liable for any damages resulting from their use. This provision may not be changed by any of our representatives.

